

DATA SHEET WEEPRO A COL

REF : WL-PC-0X



FEATURES: Coverall with collar. Elasticated hood, waist, and ankles
Knitted cuff
Self-adhesive zip flap

FABRICS AND SEAMS : White Microporous film 63^{GM2} – Serged seams 4 threads

PHYSICAL PERFORMANCE

Fabric Physical Properties	Test Method	Résultats	Class
Abrasion resistance	EN530	>400 cycles	Class 3
Flex cracking	ISO 7854 B	>50 000 cycles	Class 6
Trapezoidal Tear	ISO 9073-4	61.5 N / 28.4 N	Class 2
Tensile strength	ISO 13934-1	109 N / 47.4 N	Class 1
Puncture resistance	EN863	9.06 N	Class 1

RÉSISTANCE DU TISSU À LA PÉNÉTRATION DE LIQUIDES EN ISO 6530

Fabric Chemical Properties	Penetration	Repellency
Sulphuric Acid 30%	Class 3	Class 3
Sodium Hydroxide 10%	Class 3	Class 3
O-Xylène	Class 3	Class 2
Butan-1-ol	Class 3	Class 3

WHOLE SUIT TEST PERFORMANCE

Dry particles Type 5B Method as defined by EN ISO 13982-1:2004 + A1:2010	Pass
Light splashes Type 6B Method as defined by EN 13034 : 2005 +A1: 2009	Pass
Barrier to infective agents EN14126 : 2003	Pass
Protection factor according to EN 1073-2:2002	Class 1
Surface resistivity EN 1149-5	Pass
Seam Strength ISO 13935-2	Class 3

CHART SIZE

Size	WeeSafe reference	Body Height	Chest
M	WL-PC-02	170-176 cm	92-100 cm
L	WL-PC-03	176-182 cm	100-108 cm
XL	WL-PC-04	182-188 cm	108-116 cm
XXL	WL-PC-05	188-194 cm	116-124 cm
XXXL	WL-PC-06	192-200 cm	124-132 cm

PACKAGING

	Units	Weight	Size	Volume
Carton	50	12 KG	45 X 28 X 58 CM	0,0731 ^{M3}
Pallet	700	180 KG	80 X 120 CM	1.020 ^{M3}

GENCOD

CARTON	M	3701012801247	L	3701012801261	XL	3701012801285	XXL	3701012801308	XXXL	3701012801353
POLYBAG		3701012801230		3701012801254		3701012801278		3701012801292		3701012801346

CUSTOM CODE : 6210109800

WeeSafe – IMMEUBLE "LE FUJY"- 1 RUE DU CENTRE 93160 NOISY-LE-GRAND - FRANCE – Tél : + 33 (0)1 43 09 98 04
Courriel : contact@weesafe.fr

