

60.720M

Clean room mask

60.720L

With ties-on - tile folding



FEATURES & BENEFITS

- Low particle release level - Helmke drum tested for use in **ISO 5 Class c or higher cleanrooms**.
- Excellent filtration efficiency of particles, bacteria and viruses. (> 99 %)
- The mask adapts to users and protocols thanks to its two available sizes.
- Softex technology limits the risk of particulate contamination while reducing the risk of skin irritation for the wearer.
- Made from **50% recycled materials**.
- The adjustable and malleable nose clip prevents glasses from fogging up.
- The ISO AIR range is manufactured in a Controlled Atmosphere Zone.



PRODUCT DETAILS

Product name :	ISO AIR clean room mask
Product type :	Single use, non sterile
Shape :	Tile folding
Packaging :	6 bags of 50 masks - Double packed
Dimensions :	M - 175 x 95 mm (+/- 5mm) L - 195 x 95 mm (+/- 5mm)
Unit weight :	60.720M : 3,75 g (+/- 10%) 60.720L : 4 g (+/- 10%)
Manufacturing country :	France



Made from **50% recycled materials**, this ISO AIR mask reduces the consumption of polypropylene from fossil resources. Thanks to the Mass Balance approach and its value chain, we have designed the ISO AIR range from recycled polypropylene which, thanks to a chemical recycling process using heat, is returned to the state of monomers. This enables to keep the **same characteristics** as virgin polypropylene. It is thanks to this technique that our Mass Balance masks maintain **excellent performances**, similar to the performances of a mask made from virgin polypropylene.. For more information about Mass Balance, please contact us.

RECOMMENDED AREAS – GMP COMPLIANT

Micro & nanoelectronics / Aerospace / Laboratories / Research / Cosmetics / Medical devices / Biotechnology / Automotive

60.720M
60.720L

Clean room mask
With ties-on - tile folding



CERTIFICATIONS & STANDARDS

Helmke drum tested according to IEST-RP-CC003.4

Manufactured in an ISO 9001 certified facility

This mask is neither a Medical Device as defined in Regulation (EU) 2017/745 nor a Personal Protective Equipment as defined in Regulation (EU) 2016/425.

PRODUCT PERFORMANCE				
TEST	TESTING METHOD	LABORATORY	REPORT N° & DATE	RESULTS
DELTA P	EN 14683:2019	CENTEXBEL	22.03961.01 09/08/2022	50,9 Pa/cm ²
Bacterial Filtration Efficiency: BFE	EN 14683:2019	CENTEXBEL	22.03961.01 09/08/2022	99,9 %
Particles Filtration Efficiency 0.1 µm : PFE	ASTM F2299	NELSON	1535462-S01 09/08/2022	99,9 %
Virus Filtration Efficiency : VFE	ASTM F2101	NELSON	1535464-S01 11/08/2022	99,9 %

STORAGE CONDITIONS

Normal storage conditions: should not be exposed to moisture and sunlight, should be stored at room temperature.

Shelf life : 5 years

LOGISTICS



Outer case
spec.

Item	Size (mm)	Gross weight (kg)	QTY/ pallet
60.720M	590 x 260 x 192	1,8	48
60.720L		1,9	

Inner bag
spec.

Size (mm)	QTY / case
350 x 300 x 110	6 x 50
	300 pcs

EAN Codes

Item	Outer case	Inner bag
60.720M	3 700 381 521 893	3 700 381 521 923
60.720L	3 700 381 521 916	3 700 381 521 909