Fiche Technique

WL-CCE/AD

Chemical protective shoecovers - Type PB6 "B"
Personal Protective Equipment Cat.III

FEATURES & BENEFITS

- Very low-linting fabric preventing contamination in controlled critical environments
- Thick PVC sole with strong anti-slip performance on dry or wet floors
- Elastic bands at the ankle to keep the shoecovers securely in place
- Ideal protection against low-concentration chemical splashes, powders, adhesives, fiberglass, solvents, paints
- Three sizes available: XS, SM & LXL



Recommended uses

- Pharmaceutical and cosmetic laboratories
- Advanced industries and electronics
- Composites industry
- Food processing industry

Item	Size	Sole length	Sole width
WL-CCE/AD-XS	XS	27 cm	11,5 cm
WL-CCE/AD-SM	SM	30 cm	11,5 cm
WL-CCE/AD-LXL	LXL	36 cm	11,5 cm

PRODUCT DETAILS

Product name :	**WeePro shoecovers**
Product type :	Type PB 6
Material :	Microporous film + PVC sole
Material grammage :	63 g/m²
Sole grammage :	380 g/m²
Confection :	Elasticated at the ankle and heel
Seams :	4 threads overstitched
Color :	White
Qty / case :	400 units
Origin :	China

CERTIFICATIONS & STANDARDS

- Complies with the requirements of Regulation (EU) 2016/425 on Personal Protective Equipment
- Manufactured under an ISO 9001 certified system

WL-CCE/AD

Chemical protective shoecovers - Type PB6 "B"

Personal Protective Equipment Cat.III

COVERALL TESTS PERFORMANCES		
	Standard / Test method	**Results**
Test de pulvérisation à faible densité Type PB 6 "B"	EN 13034:2005 + A1:2009	Compliant
Protection against biological risks	EN 14126:2003 + AC:2004	Compliant
Seam strength	EN ISO 13935-2	Class 3/6

PHYSICAL PROPERTIES OF THE FABRIC		
Tests	**Test method**	**Results**
Abrasion resistance	EN 530	Class 1/6
Flex cracking resistance	ISO 7854 B	Class 4/6
Tear resistance	ISO 9073-4	Class 2/6
Tensile strength	ISO 13934-1	Class 1/6
Puncture resistance	EN 863	Class 1/6

FABRIC RESISTANCE TO PENETRATION BY LIQUIDS EN ISO 6530		
Chemicals tested	**Penetration**	**Repellency**
Sulphuric Acid 30%	Class 3/3	Class 3/3
Sodium Hydroxide 10%	Class 3/3	Class 3/3
O-Xylene	Class 3/3	Class 2/3
Butan-1-ol	Class 3/3	Class 3/3

FABRIC RESISTANCE TO PENETRATION BY INFECTIVE AGENTS EN 14126	
Resistance to penetration by contaminated liquids under hydrostatic pressure ISO 16604 / ISO 16603	Class 6/6
Resistance to penetration by contaminated liquids according to EN ISO 22610	Class 6/6
Resistance to penetration by contaminated liquid aerosols according to EN ISO 22611	Class 3/3
Resistance to penetration by contaminated solid particles ISO 22612	Class 3/3

STORAGE CONDITIONS

Normal storage and conservation conditions: Should not be exposed to moisture and sunlight, and should be stored at room temperature.

Shelf Life : 5 years

LOGISTICS

Outer case spec.

Item	Size	Size Mm	Gross weight (kg)	QTY/ pallet
WL-CCE/AD-XS	XS			24
WL-CCE/AD-SM	SM	470 x 320 x 420	11	24
WL-CCE/AD-LXL	LXL			24

Inner bag spec.

Cdt
20 x 20 units

EAN codes

Item	Outer case
WL-CCE/AD-XS	3 701 012 801 155
WL-CCE/AD-SM	3 701 012 802 015
WL-CCE/AD-LXL	3 701 012 801 162

Medicom SAS
Bld de la chanterie | 49124 Saint Barthélemy d'Anjou – France
T : 33 (0) 241 963 434 | F : + 33 (0) 241 963 453 | sales.support.pro.eu@medicom.com | www.medicom-eu.com